

CVD 5100 SERIES

COMPOSITE VIDEO MATRIX SWITCHERS

CVD 5188, CVD 5184, CVD 5144



Technical Specifications

INPUT OVERVIEW

Signal	Composite Video
Connectors	(9) BNC Female
Video Impedance	75 Ohms
Video Level	0.5 Vpp – 1.5 Vpp

OUTPUT OVERVIEW

Signal	Composite Video
Connectors	(8) BNC Female
Video Impedance	75 Ohms
Video Level	Follows Input
Bandwidth	60 MHz
Differential Gain	< 0.1%
Differential Phase	< 0.1 Degrees

CONTROL	9-Pin D-Sub Female Connector
	Front Panel Keypad
	RS232 Controllable

DISPLAY	Power On Indicator
	LCD Display Module

Physical Specifications

Dimensions	1U High, 1 Rack Wide
(inches)	1.75 H x 17.00 W x 9.50 D
(cm)	4.45 H x 43.18 W x 24.13 D
Enclosure	Aluminum, Black, Texture Finish
Weight	4.9 lbs / 2.22 kg
Input Voltage	110 or 220 VAC, 60/50 Hz, Internal
Power Dissipated	5.8 Watts

Accessories

CVD 0181	Rack Mount Ears (included)
CVD 0014	Power Cord (included)

Other Available Options

CVA 5100 Series - Composite Video with Stereo Audio Matrix Switcher