

CVD 5106

COMPOSITE VIDEO SWITCHER

6 In, 1 Out



Technical Specifications

INPUT OVERVIEW

Signal Composite Video
Connector (7) BNC Female
Video Impedance 75 Ohms
Video Level 0.5 Vpp - 1.5 Vpp

OUTPUT OVERVIEW

Signal Composite Video
Connector (1) BNC Female
Video Impedance 75 Ohms
Video Level Follows Input
Bandwidth 130 MHz
Differential Gain. < 0.1%
Differential Phase < 0.5 Degrees

CONTROL RS232 (9-Pin D-Sub Female Connector)
Front Panel Keypad
RF Remote (Optional)

DISPLAYS Power On Indicator
7-Segment Channel Readout

Physical Specifications

Dimensions 1U High, 1/2 Rack Wide
(inches) 1.75 H x 8.50 W x 6.00 D
(cm) 4.45 H x 21.59 W x 15.24 D
Enclosure Aluminum, Black, Texture Finish
Weight 1.6 lbs / 0.73 kg
Input Voltage 110 or 220 VAC Wall Mount,
12 VAC, 1A, UL
Power Dissipated. 6 Watts

Accessories

CVD 0185 Rack Mount Ears (optional)
CVD 0003 Power Supply (included)

Other Available Options

CVA 5106 - 6 In, 1 Out Composite Video with Stereo Audio Switcher