

CVD 5200 SERIES

S-VIDEO SWITCHERS

CVD 5288, CVD 5284, CVD 5244



Technical Specifications

INPUT OVERVIEW

Signal	S-Video
Connectors	(8) 4-Pin Mini Din Female (1) BNC Female
Video Impedance	75 Ohms Y/C
Video Level	0.5 Vpp – 1.5 Vpp

OUTPUT OVERVIEW

Signals	S-Video
Connectors	(8) 4-Pin Mini Din Female
Video Impedance	75 Ohms Y/C
Video Level	Follows Input
Bandwidth	60 MHz
Differential Gain	< 0.1%
Differential Phase	< 0.1 Degrees

CONTROL

9-Pin D-Sub Female Connector
Front Panel Keypad
RS232 Controllable

DISPLAY

Power On Indicator
LCD Display Module

Physical Specifications

Dimensions	1U High, 1 Rack Wide
(inches)	1.75 H x 17.00 W x 9.50 D
(cm)	4.45 H x 43.18 W x 24.13 D
Enclosure	Aluminum, Black, Texture Finish
Weight	4.4 lbs / 2.0 kg
Input Voltage	110 or 220 VAC, 60/50 Hz, Internal
Power Dissipated	10 Watts

Accessories

CVD 0181	Rack Mount Ears (included)
CVD 0014	Power Cord (included)

Other Available Options

CVA 5200 Series -- S-Video with Stereo Audio Matrix Switcher