

CVD 7176

SCAN CONVERTER



Technical Specifications

INPUT OVERVIEW

Signal	Analog RGBHV
Connector	(1) 15 pin-HD Female
Video Impedance	75 Ohms
Video Level	0.7 Vpp - 1.0 Vpp
Sync Level	TTL
Sync Polarity.	+ / -

OUTPUT OVERVIEW

Signals	VGA, RGB, Composite, S-Video
Connectors.	(1) Phono Female (RCA jack) (1) 4-Pin Mini Din Female
Video Impedance	75 Ohms
Video Level	1.0 Vpp, for Composite & S-Video 0.7 Vpp, for RGB

RESOLUTION OVERVIEW

Maximum.	1024 x 768
Recommended	800 x 600
Horizontal Scan	24 KHz to 80 KHz
Syncs	TTL Level Separate Hsync & Vsync

Physical Specifications

Dimensions	1U High, 1/2 Rack Wide
(inches)	1.75 H x 8.50 W x 6.00 D
(cm)	4.45 H x 21.59 W x 15.24 D
Enclosure.	Aluminum, Black, Texture Finish
Weight	1.2 lbs / 0.54 kg
Input Voltage	110 or 220 VAC Wall Mount, 9 VDC, 1.2 A, UL
Power Dissipated.	7.5 Watts

Accessories

CVD 0185	Rack Mount Ears (optional)
CVD 7303.	Terminated RCA to RCA Cable (included)
CVD 7304.	Terminated 4-Pin Mini Din Cable (included)
CVD 7178.	15-Pin HD to 15-Pin HD Cable (included)
CVD 0010.	Power Supply (included)