

# CVD 8210

## UNIVERSAL INTERFACE



### Technical Specifications

Signal . . . . .	Analog RGBHV
Connector . . . . .	(1) 15 pin-HD Female
Video Impedance . . . . .	75 Ohms
Video Level . . . . .	0.7 Vpp - 1.0 Vpp
Sync Level . . . . .	TTL
Sync Polarity. . . . .	+ / -

#### OUTPUT OVERVIEW

Signals . . . . .	VGA, RGB, Composite, S-Video
Connectors. . . . .	(1) Phono Female (RCA jack) (1) 4-Pin Mini Din Female
Video Impedance . . . . .	75 Ohms
Video Level . . . . .	1.0 Vpp, for Composite & S-Video 0.7 Vpp, for RGB

#### RESOLUTION OVERVIEW

Maximum. . . . .	1024 x 768
Recommended . . . . .	800 x 600
Horizontal Scan . . . . .	24 KHz to 80 KHz
Syncs . . . . .	TTL Level Separate Hsync & Vsync

### Physical Specifications

Dimensions . . . . .	1U High, 1/2 Rack Wide
(inches) . . . . .	1.75 H x 8.50 W x 6.00 D
(cm) . . . . .	4.45 H x 21.59 W x 15.24 D
Enclosure. . . . .	Aluminum, Black, Texture Finish
Weight . . . . .	1.2 lbs / 0.54 kg
Input Voltage . . . . .	110 or 220 VAC Wall Mount, 9 VDC, 1.2 A, UL
Power Dissipated. . . . .	7.5 Watts

### Accessories

CVD 0185 . . . . .	Rack Mount Ears (optional)
CVD 7303. . . . .	Terminated RCA to RCA Cable (included)
CVD 7304. . . . .	Terminated 4-Pin Mini Din Cable (included)
CVD 7178. . . . .	15-Pin HD to 15-Pin HD Cable (included)
CVD 0010. . . . .	Power Supply (included)