

## CVD 9002

### RGBHV DISTRIBUTION AMPLIFIER 1 In, 2 Out



### Technical Specifications

#### INPUT OVERVIEW

Signals . . . . .	Analog RGBHV, RGBS, RGsB, RsGsBs, YUV
Connectors . . . . .	(5) BNC Female
Video Impedance . . . . .	75 Ohms
Video Level . . . . .	0.5 Vpp - 1.5 Vpp
Sync Level . . . . .	Analog / TTL (0.5 Vpp - 5.0 Vpp)
Sync Polarity . . . . .	+ / -

#### OUTPUT OVERVIEW

Signals . . . . .	Follows Input
Connectors . . . . .	(10) BNC Female
Video Impedance . . . . .	75 Ohms
Video Level . . . . .	Follows Input
Sync Impedance . . . . .	75 Ohms
Sync Level . . . . .	TTL
Bandwidth . . . . .	350 MHz

### Physical Specifications

Dimensions . . . . .	1U High, 1/2 Rack Wide
(inches) . . . . .	1.75 H x 8.50 W x 6.00 D
(cm) . . . . .	4.45 H x 21.59 W x 15.24 D
Enclosure . . . . .	Aluminum, Black, Texture Finish
Weight . . . . .	1.9 lbs / 0.86 kg
Input Voltage . . . . .	110 or 220 VAC Wall Mount, 12 VAC, 1A, UL
Power Dissipated . . . . .	2 Watts

### Accessories

CVD 0003 . . . . .	Power Supply (included)
--------------------	-------------------------