

# CVD 9102

## COMPOSITE VIDEO DISTRIBUTION AMPLIFIER

### 1 In, 2 Out (Metal Enclosure)



### Technical Specifications

#### INPUT OVERVIEW

Signal . . . . . Composite Video  
Connector . . . . . (1) BNC Female  
Video Impedance . . . . . 75 Ohms  
Video Level . . . . . 0.5 Vpp - 1.5 Vpp

#### OUTPUT OVERVIEW

Signals . . . . . Composite Video  
Connectors. . . . . (2) BNC Female  
Video Impedance . . . . . 75 Ohms  
Video Level . . . . . Follows Input  
Bandwidth . . . . . 150 MHz

### Physical Specifications

Dimensions . . . . . 1U High  
(inches) . . . . . 1.75 H x 5.10 W x 3.50 D  
(cm) . . . . . 4.45 H x 12.95 W x 8.89 D  
Enclosure . . . . . Aluminum, Black, Texture Finish  
Weight . . . . . 1.0 lb / 0.45 kg  
Input Voltage . . . . . 110 or 220 VAC Wall Mount,  
9 VDC, 500mA, UL  
Power Dissipated. . . . . 1 Watt

### Accessories

CVD 0003. . . . . Power Supply (included)

### Other Available Options

**CVA 9102** - 1 In, 2 Out Composite Video with Stereo  
Audio Distribution Amplifier.