

CVD 9208

S-VIDEO DISTRIBUTION AMPLIFIER 1 In, 8 Out (Metal Enclosure)



Technical Specifications

INPUT OVERVIEW

Signal	S-Video
Connector	(1) 4-Pin Mini Din Female
Video Impedance	75 Ohms Y/C
Video Level	Y: 0.5 Vpp - 1.5 Vpp C: 143 m Vpp - 429 m Vpp
Coupling	AC

OUTPUT OVERVIEW

Signals	S-Video
Connectors	(8) 4-Pin Mini Din Female
Video Impedance	75 Ohms Y/C
Video Level	Y: 0.5 Vpp - 1.5 Vpp C: 143 m Vpp - 429 m Vpp
Gain Range	-6 dB to +6 dB
Coupling	DC
Bandwidth	150 MHz
Differential Gain	< 0.1%
Differential Phase	< 0.5 Degrees

CONTROL

Gain Control Knob
Calibration Select Switch
AGC Gain Select Switch
Sync Clamp Select Switch

DISPLAYS

Power On / Unity Gain Indicator

Physical Specifications

Dimensions	1U High, 1/2 Rack Wide
(inches)	1.75 H x 8.50 W x 6.00 D
(cm)	4.45 H x 21.59 W x 15.24 D
Enclosure	Aluminum, Black, Texture Finish
Weight	1.4 lbs / 0.64 kg
Input Voltage	110 or 220 VAC Wall Mount, 12 VAC, 1A, UL
Power Dissipated	10.7 Watts

Accessories

CVD 0003	Power Supply (included)
--------------------	-------------------------

Other Available Options

CVA 9208 - 1 In, 8 Out S-Video with Stereo Audio Distribution Amplifier.