

TECHNICAL SPECIFICATION

Technical Information

Product

| | |
|-----------------|---------|
| Title | NC3MX-B |
| Connection Type | XLR |
| Gender | male |

Electrical

| | |
|------------------------------|-----------------------------|
| Capacitance between contacts | ≤ 4 pF |
| Contact resistance | ≤ 3 m Ω |
| Dielectric strength | 1,5 kVdc |
| Insulation resistance | > 10 G Ω (initial) |
| Rated current per contact | 16 A |
| Rated voltage | < 50 V |

Mechanical

| | |
|------------------|--------------------------|
| Cable O.D. | 3.5 - 8.0 mm |
| Insertion force | ≤ 20 N |
| Withdrawal force | ≤ 20 N |
| Lifetime | > 1000 mating cycles |
| Wiresize | max. 2.5 mm ² |
| Wiresize | max. 14 AWG |
| Wiring | Solder contacts |
| Locking device | Latch lock |

Material

| | |
|-----------------|---|
| Boot | Polyurethan |
| Contact plating | 0.2 μ m Au hard alloy over 2 μ m Ni |
| Contacts | Brass (CuZn39Pb3) |
| Insert | Polyamide (PA 6.6 30 % GR) |
| Locking element | Zinc diecast (ZnAl4Cu1) |
| Shell | Zinc diecast (ZnAl4Cu1) |
| Shell plating | Black chromium |
| Strain relief | Polyacetal (POM) |

Environmental

| | |
|---------------------|---------------------------|
| Approvals | UL |
| Flammability | UL 94 HB |
| Standard compliance | IEC 61076-2-103 |
| Protection class | IP 40 |
| Solderability | Complies with IEC 68-2-20 |
| Temperature range | -30 °C to +80 °C |



1723 W. 4th Street Tempe Arizona 85281

P: 800.638.6104 | F: 480.966.6728 | E: sales@covid.com www.covid.com