

TECHNICAL SPECIFICATION



Technical Information

Product

Title NC3FD-LX-0

Connection Type XLR

Gender female

Electrical

Capacitance between contacts ≤ 4 pF

Contact resistance ≤ 5 m Ω

Dielectric strength 1,5 kVdc

Insulation resistance > 10 G Ω (initial)

Rated current per contact 16 A

Rated voltage < 50 V

Mechanical

Insertion force ≤ 20 N

Withdrawal force ≤ 20 N

Lifetime > 1000 mating cycles

Locking force > 20 separating force N

Wiresize max. 2.5 mm²

Wiresize max. 14 AWG

Wiring Solder contacts

Locking device Retention spring

Chassis shape D

Material

Contact plating 2 μ m Ag over 2 μ m Ni

Contacts Bronze (CuSn6)

Insert Polyamide (PA 6.6 30 % GR)

Locking element Steel Ck67

Shell Zinc diecast (ZnAl4Cu1)

Shell plating Nickel

Environmental

Flammability UL 94 HB

Standard compliance IEC 61076-2-103

Protection class IP 40

Solderability Complies with IEC 68-2-20

Temperature range -30 °C to +80 °C



1723 W. 4th Street Tempe Arizona 85281

P: 800.638.6104 | F: 480.966.6728 | E: sales@ covid.com www.covid.com