

TECHNICAL SPECIFICATION



Technical Information

Product

Title NC3FD-LX-HA-BAG

Connection Type XLR

Gender female

Electrical

Capacitance between contacts ≤ 4 pF

Contact resistance ≤ 5 m Ω

Dielectric strength 1,5 kVdc

Insulation resistance > 10 G Ω (initial)

Rated current per contact 1 A

Rated voltage < 50 V

Mechanical

Insertion force ≤ 20 N

Withdrawal force ≤ 20 N

Lifetime > 1000 mating cycles

Wire size 0.22 - 0.34 mm²

Wire size 24 - 22 AWG

Wiring Crimp contacts

Locking device Latch lock

Chassis shape D

Material

Contact plating 2 μ m Ag over 2 μ m Ni

Contacts Bronze (CuSn6)

Insert Polyamide (PA 6.6 30 % GR)

Locking element Steel Ck67

Shell Zinc diecast (ZnAl4Cu1)

Shell plating Black chromium

Environmental

Flammability UL 94 HB

Standard compliance IEC 61076-2-103

Protection class IP 40

Temperature range -30 °C to $+80$ °C



1723 W. 4th Street Tempe Arizona 85281

P: 800.638.6104 | F: 480.966.6728 | E: sales@covid.com www.covid.com