## TECHNICAL SPECIFICATION P-HDA30-XX



Description: Active Optical HDMI 48G, 8K Ultra HD, Distances up to 100ft, Plenum

Why Use This Product: The AOC HDMI cable is the perfect choice for high resolution digital video applications up to 100ft.

#### **Key Features**

- Plenum Rated
- HDMI 2.1 Cable | 48Gbps
- Supports HDR10 and resolutions up to 4320p@60Hz (8K)
- DSC 1.2 resolutions up to 8K@120Hz and 10K@120Hz
- Active Optical Cable (Fiber-Copper Hybrid)
- eARC support for Dolby Atmos, DTS-X 5.1/7.1 Lossless, Dolby TrueHD, and DTS-HD Surround Sound
- Supports CEC commands and ARC features
- Supports Deep Color and x.v.Color
- EDID, CEC, HDCP compliant
- Covid T-Grip<sup>™</sup> Connectors (16lbs of retention force)





HDMI 2.1 AOC CABLE, 48G Plenum

Part Number:	P-HDA30-XX
Revision Number:	4
Date:	11-16-2023
Page Number:	1 of 2

1723 W. 4th Street Tempe Arizona 85281


P: 800.638.6104 | F: 480.966.6728 | E: sales@covid.com | www.covid.com

# TECHNICAL SPECIFICATION P-HDA30-XX



### **Technical Specifications**

Maximum Video Settings	4K@144Hz and 8K@60Hz
Maxiumum DSC Resolutions Connectors Connector Hood	8K@120Hz and 10K@120Hz
Connectors	HDMI - Type A
Connector Hood	Metallic, Black/Silver
Bandwidth Cable Type Cable Jacket Outer Diameter	48Gbps (4x12Gbps per channel)
Cable Type	Hybrid with OM3 fiber and copper wire
Cable Jacket	Plenum, Black
Outer Diameter	0.18in
Minimoura Donal Dadius	1 0:
Operating/Storage Temperature	40°C ~ + 70°C
Operating Humidity	10% ~ 80% KH
Number of Connector Mating Cycles	3000
Number of Connector Mating Cycles  Available Lengths  Power Supply Voltage	25ft, 35ft, 50ft, 75ft, 100ft
Power Supply Voltage	4.75v ~ 5.25v
Differential Input	100 ohm (typ)
Differential Input Power Consumption	250mW (max)



### HDMI 2.1 AOC CABLE, 48G Plenum

Part Number:	P-HDA30-XX
Revision Number:	4
Date:	11-16-2023
Page Number:	2 of 2