

TECHNICAL SPECIFICATION

USBCA20



Description: USB Type-C active optical cable, supports audio/video/data/charge, lengths up to 49 ft

Why Use This Product: This full-featured Type-C AOC active optical cable offers adaptive support for 4 lane DP 1.2 + USB 2.0 or 2 lane DP 1.2 + USB 3.2 10G up to 49 ft. Utilizing fiber optic technology for high-speed signal transmission and copper wire for low-speed signal transmission and power supply, this cable solves the problem of traditional copper wire not being able to transmit signals over long distances.

Key Features

- USB 3.2 Gen 2 Type-C (10 Gbps)
- Backward Compatible with USB 2.0/1.1
- Full-Featured (Audio/Video/Data/Charge Support)
- Automatic Mode Switching Between:
 - 4-Lane DP 1.2 + USB 2.0 (480 Mbps)
 - 2-Lane DP 1.2 + USB 3.2 (10 Gbps)
- Supports DP Alt Mode 1.2 (4K 60Hz)
- Supports 100W PD + Fast Charging
- Supports cable lengths of up to 15m (49ft)
- Supports Touch Screen Operation
- Fiber Optic + Copper Hybrid Cable
- E-Mark Chip Ensures Stable Current and Reliability
- Adaptive DP Alt Mode Switching (Plug and Play)
- No External Power Needed



USB-C 3.2 Gen 2 (10G) Active Optical Cable Non-Plenum

Part Number:	USBCA20
Revision Number:	2
Date:	6-25-2026
Page Number:	1 of 2

1723 W. 4th Street Tempe Arizona 85281
P: 800.638.6104 | F: 480.966.6728 | E: sales@covid.com | www.covid.com

Disclaimer: Conditions of use may vary. Information is subject to change without notice.

TECHNICAL SPECIFICATION

USBCA20



Technical Specifications

USB Version.....USB 3.2 Gen 2
 USB Transfer Rate.....10 Gbps
 DP Transfer Rate.....Supports 4 Lane DP 1.2 or 2 Lane DP 1.2
 Max Video Resolution.....DP 1.2: 4K 60Hz
 Wave Length.....850nm
 Available Cable Lengths.....25ft, 33ft, 49ft
 ESD Protection.....IEC 61000-4-2: ± 8kV (Air-Gap Discharge) & ± 4kV (Contact Discharge)

Connection Specifications

Input.....1x Source (USB Type-C, Male)
 Output.....1x Display (USB Type-C, Male)

Mechanical Specifications

Outer Diameter.....6.5mm
 Cable Color.....Black
 Conductor.....Optical Fiber + Tinned Copper
 Chip.....Optoelectronic Conversion Chip
 Jacket.....PVC
 Connector Casing.....Metal Enclosure
 Connector Color.....Nickel-Plated
 Power Supply.....Metal Enclosure
 Working Voltage.....5V ± 0.25
 Charge Power.....Supports Fast Charging PD 3.0 20V / 5A (5m at 90W, 10m / 15m at 85W)
 Operation Temperature.....0°C ~ 40°C / 32°F ~ 104°F
 Storage Temperature.....-20°C ~ 60°C / -4°F ~ 140°F
 Operating Humidity.....20% ~ 80% (Relative Humidity, Non-Condensing)
 Storage Humidity.....10% ~ 90% (Relative Humidity, Non-Condensing)

USB-C 3.2 Gen 2 (10G) Active Optical Cable Non-Plenum

Part Number:	USBCA20
Revision Number:	2
Date:	6-25-2026
Page Number:	2 of 2

1723 W. 4th Street Tempe Arizona 85281
 P: 800.638.6104 | F: 480.966.6728 | E: sales@covid.com | www.covid.com